

**WERDEN®**

**WE-4017**  
**FUSIBLE FOTOVOLTAICA**  
**10 X 38 20A**



| DENOMINACIÓN                   | DATOS TÉCNICOS                        |
|--------------------------------|---------------------------------------|
| Norma:                         | IEC 60269-6                           |
| Tamaño:                        | 10x38                                 |
| Categoría de utilización:      | gPV                                   |
| Tensión nominal:               | 1000V DC                              |
| Capacidad de ruptura nominal:  | 20 kA                                 |
| Tiempo constante:              | 1-3 ms                                |
| Corriente nominal :            | 20A                                   |
| Temperatura de funcionamiento: | -40°C ~ + 90°C (humedad relativa 90%) |

| CORRIENTE NOMINAL | PREARCO |     |
|-------------------|---------|-----|
| 1                 | 0.15    | 0.4 |
| 2                 | 1.2     | 3.3 |
| 3                 | 3.9     | 11  |
| 4                 | 10      | 27  |
| 5                 | 18      | 48  |
| 6                 | 31      | 89  |
| 8                 | 3.1     | 31  |
| 10                | 7.2     | 68  |
| 12                | 16      | 136 |
| 15                | 24      | 215 |
| 16                | 28      | 255 |
| 20                | 38      | 392 |
| 25                | 71      | 508 |
| 30                | 102     | 821 |
| 32                | 176     | 976 |



**RoHS**